

LIPPMANN J3055 JAW CRUSHER

Lippmann designed its new 3055 jaw crusher as a lighter-weight, contractor-friendly crushing solution that doesn't sacrifice productivity and reliability. The Lippmann 3055 gives customers a durable crusher with added focus on portability, serviceability, and safety, making it an excellent addition to any rental fleet.

**PRODUCT FEATURES**

- Fabricated and stress relieved frame
- One-piece, cast steel swing jaw
- Dual pick points for swing jaw lifting
- Swing jaw servicing cylinder to move swing jaw forward
- Taper roller swing jaw bearings
- Spherical roller frame bearings
- Grease lubrication
- Universal, fully-grooved flywheels
- Dual wedge with hydraulic assist CSS adjustment
- Automatically maintained hydraulic assist tension rod adjustment
- Jaw die ignite device to eliminate manganese welding
- Bolt-in, replaceable toe protector/die wedge
- Cast manganese die extensions
- Cast manganese cheek plates
- Ball and socket type toggle bearings
- Single piece toggle bearing/block
- Bolted wedge swing jaw toggle bearing retention
- Spring base cutout for ease of install and tension rod maintenance


PRODUCT SPECIFICATIONS

FEED OPENING	30"X55"	SWING DIE LENGTH	65"
ELECTRIC HP	200	STATIONARY DIE LENGTH	58.5"
FLYWHEEL SPEED	250 RPM	SHAFT DIA. CENTER	13.625"
DISCHARGE OPENING	3"-7"	SHAFT DIA. SWING BEARING	11.8"
WEIGHT (LBS.)	57,500	SHAFT DIA. FRAME BEARING	10.25"
FLYWHEEL DIAMETER	54"	SHAFT THROW	1.5"

Lippmann Milwaukee, Inc.
 3271 East Van Norman Avenue
 Cudahy, WI 53110-0586
 (800) 648-0486 • (414) 744-2565
 Fax: (414) 744-8172
www.lippmann-milwaukee.com

Sold and serviced by:

The information contained in this literature is meant to be general in nature and is not intended to be used for specific application, construction, or installation purposes. Please note that machine capacities, settings, and other application considerations can vary from the information contained in this literature, depending on the material being crushed, moisture, feed sizes, other materials in the feed, etc. As a result, no warranty of any kind, either expressed or implied, is extended with the information contained in this literature. Lippmann Milwaukee, Inc. expressly reserves the right to change specifications or designs without prior notice or obligation.