## THE **IO60j-t** QUALITY MATERIAL OUTDOES THE COMPETITION



The 1060j-t packs the same performance as the 1200j as an incredibly commanding and resilient jaw crusher. Load up capacities in excess of 400 TPH and produce high quality material in ways the competition's crushers just can't match.

- 1060mm wide x 700mm single toggle jaw
- Choice of CAT of Volvo, LRC or T4F/Stage V engines
- · HD crawler tracks
- · Fast setup time

- Integrated hydraulic folding hopper
- Integrated hydraulic folding stockpiling conveyors
- I-beam plate fabricated chassis construction
- · Quick release jaw for transport
- Large gap between crusher discharge and main conveyor feedboot
- Open chassis design for ease of maintenance



## 1060j-t TECHNICAL SPECIFICATIONS

SPECIFICATIONS	
Feed Opening	42" (1060mm)
Crusher Drive	Hydraulic - V-Belt
Min. Opening	2.8" (70mm)
Max. Opening	8" (200mm)
CSS Adjustment	Hydraulic Wedges
Level Sensor	Ultrasonic

HOPPER	
Hopper Length	13' 8.3" (4175mm)
Hopper Width	8' (2342mm)
Hopper Volume	7.6 yd³ (5.8m³)

FEEDER	
Feeder Width	41.9" (1064mm)
Adjustable Speed	YES - Via Electrical Proportional
Drive	Hydraulic

TOTAL WEIGHT	
Total Weight	106,900 lbs (48,500kg)

ENGINE	
Engine Option 1	Volvo D11 T4F/Stage V, 360 hp (270kW)
Engine Option 2	CAT C9.3B T4F/Stage V, 416 hp (310kW)
Engine Option 3	CAT C9.3 LRC, 416 hp (310kW)
Engine Speed	1800 rpm
Fuel Tank Capacity	141 US gal (535L)
Hydraulic Tank Capacity	272 US gal (1030L)

DIMENSIONS	
Transport Length	53' 2" (16.20m)
Transport Width	9' 6" (2.90m)
Transport Height	11' 5.8" (3.50m)
Operating Length	50' 8" (15.44m)

CONVEYOR	
Stockpile Height	12' 10" (3912mm)
Belt Width	48" (1200mm)
Angle Adjustable	YES
Quick Release	YES

## LIPPMANN

3271 East Van Norman Avenue Cudahy, WI 53110

Lippmann-Milwaukee.com

800-648-0486

AUTHORIZED DISTRIBUTOR