

PORTABLE CONE CRUSHER

THE **300c-wr** EXCEEDS YOUR PRODUCTIVITY NEEDS



The wheeled 300c-wr cone crusher boasts a highly productive 44" cone and unbeatable versatility thanks to the complete closed-circuit screening and recirculating system. The crusher's high material capacity and throughput, along with large stockpile capacity, allow operators to produce a high-quality crushed and screened final product with a single machine.

- Lockable - 8hp electric start Honda powered hydraulic power pack
- Individual wheel fenders
- 2x manually lowered front support legs
- 4x hydraulic run-on jack legs
- 2x drop down crib legs
- Overflow chute
- Storage for cone feed chute for transport
- Metal detecting dump chute, to remove metal objects for cone feed
- Flop gate and lined chute to pull material from mid-deck as specified product

LIPPMANN

300c-wr TECHNICAL SPECIFICATIONS

CRUSHING CHAMBER	
Feed Opening	8.31" (211mm)
Crusher Drive	2x Banded V-Belts
Min. Opening	0.50" (13mm)
Max. Opening	0.75" (19mm)
CSS Adjustment	Hydraulic
Level Sensor	YES

REAR DISCHARGE CONVEYOR	
Stockpile Height	12' 1" (3.68m)
Width	48" (1219mm)
Length	89" (2261mm)
Speed	380 ft/m (116m/m)
Angle Adjustment	YES

TOTAL WEIGHT	
Total Weight	138,200 lbs (62.686kg)

HOPPER	
Hopper Length	190" (4826mm)
Hopper Width	82" (2083mm)
Hopper Volume	370 ft³ (10m³)

FEED CONVEYOR	
Width	47" (1194mm)
Length	174" (4420mm)
Speed	64 f/m (19.5m/m)
Drive	Hydraulic - Gearbox Reducer

POWER	
Panel	Wired to terminal box w. opt NEMA-12 motor control center
Voltage	460V 575V
Hydraulic Tank Capacity	84.5 US gal (320L)

LIPPMANN

3271 East Van Norman Avenue
Cudahy, WI 53110
Lippmann-Milwaukee.com
800-648-0486

AUTHORIZED DISTRIBUTOR